Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at https://www.ul.com/about/locations.

Roofing Systems

COMPANY
DYME Metals Association LLC
3201 Se Dominica Ter
Stuart, FL 34997-5719 United States

R42148

Coated steel and aluminum panels identified as: "DM Class 500", "DM Class 1000", "DM Class 1050", "DM Class 1500", "DM Class 1700", "DM Class 1750", "DM Class 2000", "DM Class 1150".

BUILDING UNITS

Class A

1. **Deck:** C-15/32 **Incline:** Unlimited

Underlayment (optional): — One or more plies Polyglass USA Inc “Polystick-XFR”, self-adhered.
Base Sheet: — One ply type 30 base sheet, mechanically fastened.
Ply Sheet: — One ply GAF "VersaShield Underlayment" mechanically fastened.
Surfacing: — Minimum 26 ga. coated steel roofing panels, mechanically fastened.

2. **Deck:** C-15/32 **Incline:** Unlimited

Underlayment (optional): — One or more plies Polyglass USA Inc “Polystick-XFR”, self-adhered.
Base Sheet: — One ply type 30 base sheet, mechanically fastened.
Ply Sheet: — Two plies GAF "VersaShield Underlayment" mechanically fastened.
Surfacing: — Minimum 0.032 aluminum roofing panels, mechanically fastened.

3. **Deck:** C-15/32 **Incline:** Unlimited

Underlayment (optional): — One or more plies Polyglass USA Inc “Polystick-XFR”, self-adhered.
Base Sheet: — One ply type 30 base sheet, mechanically fastened.
Ply Sheet: — One or more layers GAF "VersaShield® Solo™ Fire Resistant Slip Sheet", mechanically fastened.
Surfacing: — Minimum 26 ga. coated steel or minimum 0.032 aluminum roofing panels, mechanically fastened.

4. **Deck:** C-15/32 **Incline:** Unlimited

Underlayment (optional): — One or more plies Polyglass USA Inc “Polystick-XFR”, self-adhered.
Base Sheet: — Two layers Atlas Roofing Corp "FR50".
Ply Sheet: — One ply type 30 underlayment, mechanically fastened.
Surfacing: — Minimum 28 ga. coated steel roofing panels, mechanically fastened.

5. **Deck:** N/A **Incline:** Unlimited

Surfacing: — Minimum 26 ga. coated steel or minimum 0.032 aluminum roofing panels, mechanically fastened.

6. **Deck:** C-15/32 **Incline:** Unlimited

Base Sheet: — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat, mechanically fastened.
Underlayment: — Two plies "Polystick XFR" self-adhered.
Insulation (optional): — Any UL Classified polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness mechanically fastened or adhered with any UL Classified insulation adhesive.
Ply Sheet (optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat, mechanically fastened.
Surfacing: — Minimum 0.032 aluminum roofing panels, mechanically fastened.

7. **Deck:** C-15/32 **Incline:** Unlimited

Base Sheet: — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat, mechanically fastened.
Underlayment: — Two plies "Polystick XFR" self-adhered.
Insulation (optional): — Any UL Classified polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness mechanically fastened or adhered with any UL Classified insulation adhesive.
Ply Sheet (optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat, mechanically fastened.
Surfacing: — Minimum 26 ga. coated steel roofing panels, mechanically fastened.

8. **Deck:** C-15/32 **Incline:** Unlimited **Impact:** 4

Base Sheet (optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat, or "PolyAnchor UDL 40" mechanically fastened, or “Polystick XFR”, "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X", “Polystick® IR-Xe”, or “PolyVap SA G” self-adhered.
Underlayment: — One ply "Polystick XFR" self-adhered.
Insulation (optional): — "Polytherm" or "Polytherm-H" or any UL Classified polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness mechanically fastened or adhered with any UL Classified insulation adhesive.
Ply Sheet (optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X", “Polystick® IR-Xe”, or “PolyVap SA G” self-adhered.
Surfacing: — Minimum 26 gauge coated steel standing seam panels, mechanically fastened.

9. **Deck:** C-15/32 **Incline:** Unlimited

Base Sheet (optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or "PolyAnchor UDL 40" mechanically fastened or "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X", “Polystick® IR-Xe”, or “PolyVap SA G” self-adhered.
Underlayment: — Two plies "Polystick XFR" self-adhered.
Insulation (optional): — "Polytherm" or "Polytherm-H" or any UL Classified polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness mechanically fastened or adhered with any UL Classified insulation adhesive.
Ply Sheet (optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X", “Polystick® IR-Xe”, or “PolyVap SA G” self-adhered.
Surfacing: — Minimum 0.032 aluminum roofing panels, mechanically fastened.

Class C

1. **Deck:** C-15/32 **Incline:** Unlimited

Underlayment (optional): — One or more plies Polyglass USA Inc “Polystick-XFR”, self-adhered.
Base Sheet: — One ply type 30 base sheet, mechanically fastened.
Surfacing: — Minimum 26 ga. coated steel or minimum 0.032 aluminum roofing panels, mechanically fastened.

MAINTENANCE AND REPAIR SYSTEMS

Class A, B, or C

1. **Deck:** C-15/32 **Incline:** Unlimited

Exiting System: — Any Class A, B or C metal roof deck panel system to retain existing Certification

Surfacing: — Coated steel or aluminum roofing panels, mechanically fastened.
Underlayment (optional): — One or more plies Polyglass USA Inc “Polystick-XFR”, self-adhered.

Last Updated on 2026-06-17

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."